



### The most versatile solution for high-performance inflatable cushioning

# FillTeck Market Inflatable Packaging System

Customize the height and length of your cushion size with the touch of a button

## Versatile and flexible Performance Cushioning



FillTeck<sup>™</sup> inflatable cushioning systems provide custom performance cushioning for products of any shape and size. With the touch of a button, the operator has the ability to specify the height and length of the cushioning material. The versa-

tility of FillTeck<sup>™</sup> systems allows you to work on-line or batch material off-line.

#### Customize material height and length



A user-friendly control pad allows you to customize the height of FillTeck<sup>™</sup> packaging from 12.5 mm to 100 mm, which reduces material usage and provides protection even in narrow spaces. Material is perforated or cut to a desired length, which

eliminates waste and creates superior cushioning around your entire product.

#### Create on-demand cushioning

FillTeck<sup>™</sup> systems produce material on-demand, making them ideal for batching applications. Batched material rolls can be distributed to individual pack stations when and where they are needed. Material can also be used for packaging on a conveyor.

#### Choose the ideal material shape



The shape of FillTeck<sup>™</sup> packaging can be changed at the touch of a button to provide maximum protection for your application. To wrap a product in FillTeck<sup>™</sup> packaging, choose one of the quilted options which allow for the material to conform to irregularly shaped products. For bottom, top and side cushioning, create a protective pad by choosing an option with long cushions.

#### Unparalleled strength and performance

FillTeck<sup>™</sup> systems utilize three different film types. FillTeck<sup>™</sup> Standard is designed for light-duty cushioning applications. FillTeck<sup>™</sup> Plus film provides additional strength for fragile items. FillTeck<sup>™</sup> X film is for heavy products that require durable protection. A Sealed Air representative will help you select the right film for your application.



FillTeck <sup>™</sup> X film – out standing strength for heavy items

#### Superior bottom pad cushioning

FillTeck<sup>™</sup> inflatable cushioning systems automatically produce cushioned pads in the length and height that you desire, enabling you to provide protection at the bottom of a carton. Guarding against shock, vibration and damage, the FillTeck<sup>™</sup> inflatable cushioning systems ensures that your item arrives damage-free.

| Specifications  |  |   |
|---|--|---|
| FillTeck * 400 System<br>Special Order FillTeck * 600 System<br>1440 mm<br>170 mm<br>170 mm<br>170 mm<br>170 mm<br>170 mm<br>170 mm |  |   |
| Electrical:   | 220-240 V ~ Single Phase<br>8A 50/60 Hz                      | 220-240 V ~ Single Phase<br>8A 50/60 Hz |
| Receptacle type   | CE - IP55, 16A - 6h - 2P +<br>+<br>-<br>-<br>, 200 - 250Volt | CE - IP55, 16A - 6h - 2P +              |
| Pneumatic   | 1,8 KVA - 0,8 KW/h   | 1,8 KVA - 0,8 KW/h                      |
| Pressure minimum  | 6 bar  | 6 bar                                   |
| Output minimum  | 240 Ltr/Min (FAD)*   | 240 Ltr/Min (FAD)*                      |
| Receiver minimum  | 75 Ltrs  | 75 Ltrs                                 |
| Weight  | 380 kg   | 412 kg                                  |
| Film width  | 420 mm   | 620 mm                                  |
| Size (LWH)  | 980 mm x 1170 mm x<br>1440 mm                                | 1170 mm x 1170 mm x<br>1440 mm          |

\* (FAD) = Free Air Delivery



Protective Packaging

Telford Way, Kettering, Northants NN16 8UN, UK Tel: +44 (0) 1536 315700 Fax: +44 (0) 1536 410576 E-mail: EPDeuromktg@sealedair.com www.sealedair-emea.com Distributed by:



FT-GB-08-06

**Idee.sk s.r.o.** L.Stančeka 1279/5-11 Prievidza 97101, Slovensko

Tel: +421 907 181 517 E-mail: juraj.balaz@idee-dizajn.sk www.idee.sk

Our Products Protect Your Products